



PIN	CONNECTION	PIN
1	Not connected	1
7	Ground	4
8	Output	5
14	Supply	8

Features

- ▶ Standard frequencies held in stock
- ▶ Express manufacturing service
- ▶ Custom frequencies easily available
- ▶ Low cost for volume applications
- ▶ Industrial temperature range option

Specifications

GXO-U100F: Full size (14 pin DIL)

GXO-U100H: Half size (8 pin DIL)

Parameters	Variant		Option Codes
	F	H	
Package style: 14 pin DIL (full size) 8 pin DIL (half size)	■	■	
Frequency range: 125kHz ~ 160MHz	■	■	
Frequency stability: ±100ppm ±50ppm ±25ppm Other	■ □ □ □	■ □ □ □	B A specify
Operating temperature range: 0 to +70°C -40 to +85°C	■ □	■ □	I
Storage temperature range: -55 to +125°C	■	■	
Supply voltage (V_{DD}): +5.0V (±5%)	■	■	
Supply current (max): 15mA (125kHz ~ 0.99MHz) 20mA (1.0 ~ 5.0MHz) 25mA (>5.0 ~ 24.0MHz) 30mA (>24.0 ~ 70.0MHz) 40mA (>70.0 ~ 90.0MHz) 50mA (>90.0 ~ 160MHz)	■ ■ ■ ■ ■ ■	■ ■ ■ ■ ■ ■	
Driving ability: 50pF HCMOS / 10 LSTTL (<50.0MHz) 30pF HCMOS / 5 LSTTL (>50.0MHz)	■ ■	■ ■	
Output voltage: '0' level = 0.4V max '1' level = 90% V _{DD} min	■ ■	■ ■	
Start up time: 10ms max	■	■	
Rise / fall times: 6ns max (<80.0MHz) 5ns max (>80.0MHz)	■ ■	■ ■	
Waveform symmetry @ 50% V_{DD}: 45:55 max (<50.0MHz) 40:60 max (>50.0MHz)	■ ■	■ ■	

■ Standard. □ Optional - Please specify required code(s) when ordering

Ordering Information

Product name + variant + option codes (if any) + frequency
e.g: **GXO-U100F 40.0MHz** ±100ppm 0+70°C (standard)

GXO-U100F/BI 40.0MHz ±50ppm -40+85°C

Option code X (eg GXO-U100F/X) denotes a custom spec.

♦ Gull wing version available for SM. Refer to our website for details.