


SOLDER PAD LAYOUT

PAD	CONNECTION
1	Not connected or Enable/Disable
2	Ground
3	Output
4	Supply



Scale 2:1

Specifications

Parameters	Product	Option Codes
	GXO-613	
Frequency range:	1.50 ~ 80.0MHz	
Frequency stability:	±100ppm ±50ppm	B
Operating temperature range:	0 to +70°C -40 to +85°C	I
Storage temperature range:	-55 to +125°C	
Supply voltage (V _{DD}):	+3.3V (±0.3V)	
Supply current (max):	6mA (1.50 ~ 10.0MHz) 10mA (>10.0 ~ 26.0MHz) 15mA (>26.0 ~ 28.0MHz) 25mA (>28.0 ~ 40.0MHz) 35mA (>40.0 ~ 70.0MHz) 45mA (>70.0 ~ 80.0MHz)	
Logic levels:	'0' level = 10%V _{DD} max '1' level = 90%V _{DD} min	
Start up time:	10ms max	
Waveform symmetry:	45:55 max @ 50%V _{DD} 40:60 max @ 1.4V	
Driving ability:	30pF HCMOS / 5 TTL	
Rise / fall time:	6ns (1.50 ~ 36.0MHz) 4ns (>36.0 ~ 80.0MHz)	
Enable / disable function:	Tristate (control via pad 1)	

■ Standard. □ Optional - Please specify required code(s) when ordering

Features

- ▣ Frequencies up to 80.0MHz
- ▣ Plastic moulded package
- ▣ Enable / disable tristate function
- ▣ Wide temperature range available

Standard Frequencies

Frequencies in MHz		
1.84320	10.00000	25.00000
2.45760	12.00000	32.00000
3.68640	14.31818	40.00000
4.00000	16.00000	48.00000
4.91520	16.38400	50.00000
5.00000	19.66080	60.00000
6.00000	20.00000	64.00000
8.00000	24.00000	66.66600

Other frequencies available. Please consult our sales office.

Enable / Disable Function

Input (pad 1)	Output (pad 3)
Open	Enabled
'1' level	Enabled
'0' level	High Impedance

Ordering Information

Product name + option codes (if any) + frequency
 eg: **GXO-613 20.0MHz**
GXO-613/I 64.0MHz ±100ppm -40+85°C
 Option code X (eg GXO-613/X) denotes a custom spec.

- ◆ Available on T&R - 1k pcs per reel.
- ◆ Refer to our website for T&R and soldering details.