

GVXO-338K

CMOS 2.8V surface mount VCXO with

low current consumption

- Low current consumption
- 2.8V supply
- Miniature SM package
- Competitive pricing



CONFIGURABLE OPTIONS	
Parameter	Option Code
Frequency	
Frequency pullability	
±90ppm min	R
±100ppm min	S
Frequency stability	
* see note below	
Any	
±50ppm max	В
±25ppm max	С
Operating temperature range	
Any	
-20 to +70°C	
-40 to +85°C	I


^{*} Frequency stability is inclusive of calibration @ 25°C, operating temperature range, supply voltage change, load change and first year ageing, with V_{CTL} = 50%V_{DD}





SPECIFICATIONS

Frequency range	1.250 ~ 100.0MHz
Dimensions	3.2 x 2.5 x 1.15mm
Voltage control	+1.4V ±1.35V, 10% linearity
Storage temperature range	-40 to +85°C
Supply voltage (V _{DD})	+2.8V (±5%)
Supply current	9mA max
Driving ability	15pF CMOS
Logic levels	'0' level = 10%V _{DD} max
	'1' level = 90%V _{DD} min
Waveform symmetry	40:60 max @ 50%V _{DD}
Rise / fall time	5ns max
(20%~80%V _{DD})	
Start up time	10ms max
Net mass	27.1mg

PACKAGE DRAWING







PAD	CONNECTION
1	Control voltage
2	Ground
3	Output
4	Supply

Dimensions in mm




MARKING

FREQUENCY DC • PARTNO Pin 1 Marking type: Laser

DC = Date Code in YM, eg. "GF" = Jun 2017


	_											
	Α	В	С	D	Е	F	G	н	J	К	L	м
Y	1	2	3	4	5	6	7	8	9	0		
м	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec

SOLDERING PROFILE



Lead free solderability limits: 260°C ±5°C x 10s ±5s x 2.

TAPE & REEL SPECIFICATION



Dimensions in mm

HANDLING & STORAGE



Human Body Model (HBM) 1A (250V to <500V)

Moisture Sensitivity Level (MSL): 1 (or not applicable)



CONSTRUCTION

Ceramic body with gold-plated pads Metal lid Seam sealed

COMPLIANCE

Please refer to our **DOCUMENTS** section for more information.



PG Lead-free (< 0.1% by weight)



RoHS compliant with no exemptions.



REACH compliant.



AulTa Sn W Free of conflict minerals.



Free from halogens.



Free from ozone-depleting substances.