

SAW Filter: 2140.0MHz

Model: TA1587A

Part No: MP05544

Rev No: 1

A. MAXIMUM RATING:

Electrostatic Sensitive Device (ESD)

1. Input Power Level: 10dBm
2. DC Voltage: 3V
3. Operating Temperature: -30°C to +85°C
4. Storage Temperature: -40°C to +85°C

B. ELECTRICAL CHARACTERISTICS:


1. Terminating source impedance (single ended): $Z_S = 50\Omega$
2. Terminating load impedance (single ended): $Z_L = 50\Omega$

Item	Unit	Min.	Typ.	Max.	Note
Center frequency F_c	MHz	-	2140	-	-
Insertion Loss (2130 ~ 2150MHz) IL	dB	-	2.3	3.5	-
Amplitude Ripple (2130 ~ 2150MHz)	dB	-	0.6	1.5	-
VSWR (2130 ~ 2150MHz)		-	1.7	2.2	-
Attenuation (reference level from 0dB)					
1880 ~ 2040MHz	dB	35	39	-	-
2215 ~ 2400MHz	dB	40	45	-	-
Temperature Coefficient of Frequency	ppm/°C	-	-36	-	-


SAW Filter: 2140.0MHz
Part No: MP05544

Model: TA1587A
Rev No: 1


C. OUTLINE DRAWING:



D. MEASUREMENT CIRCUIT:





E. PCB FOOTPRINT:



SAW Filter: 2140.0MHz
Part No: MP05544

Model: TA1587A
Rev No: 1

F. FREQUENCY CHARACTERISTICS:




SAW Filter: 2140.0MHz
Part No: MP05544


Model: TA1587A
Rev No: 1

Reflection Functions

S11



S22




SAW Filter: 2140.0MHz
Part No: MP05544

Model: TA1587A
Rev No: 1


G. PACKING:

1. Reel Dimension

(Please refer to FR-75D10 for packing quantity)



2. Tape Dimension



SAW Filter: 2140.0MHz
Part No: MP05544

Model: TA1587A
Rev No: 1

H. RECOMMENDED REFLOW PROFILE:

1. Preheating shall be fixed at 150 ~ 180°C for 60 ~ 90 seconds.
2. Ascending time to preheating temperature 150°C shall be 30 seconds min.
3. Heating shall be fixed at 220°C for 50 ~ 80 seconds and at 245 ~ 260°C peak (min. 10sec).
4. Time: 2 times.

