

SAW Filter 315.0MHz
Part No: MP07597

Model: TA0657C
Rev No: 2

A. MAXIMUM RATING:

Electrostatic Sensitive Device (ESD)

1. Input Power Level: 10dBm
2. DC voltage: 3V
3. Operating Temperature: -40°C to 85°C
4. Storage Temperature: -40°C to +85°C


B. CHARACTERISTICS:

Item	Unit	Min.	Typ.	Max.
Center frequency Fc	MHz	-	315	-
Insertion loss (314.70 ~ 315.30MHz) IL	dB	-	1.52	2.5
Amplitude ripple (314.70 ~ 315.30MHz)	dB	-	0.4	1.2
VSWR (314.70 ~ 315.30MHz)	-		1.4	1.6
Attenuation (Reference level from IL dB)				
270.0 ~ 286.0MHz	dB	55	65	-
293.0 ~ 293.9MHz	dB	53	60	-
304.0 ~ 304.6MHz	dB	48	60	-
325.4 ~ 326.0MHz	dB	24	30	-
336.1 ~ 337.0MHz	dB	36	52	-
357.5 ~ 358.70MHz	dB	50	60	-
Source impedance Z _S	Ω	-	50	-
Load impedance Z _L	Ω	-	50	-
Temperature coefficient	ppm/k	-	-36	-

Notes:

1. No matching network required for operation at 50Ω.
2. For SiO₂ coating.



C. MEASUREMENT CIRCUIT:



SAW Filter 315.0MHz
Part No: MP07597

Model: TA0657C
Rev No: 2


D. FREQUENCY CHARACTERISTICS:



SAW Filter 315.0MHz
Part No: MP07597


Model: TA0657C
Rev No: 2

E. OUTLINE DRAWING:



B: Input
E: Output
A, C, D, F: Ground
Unit: mm

F. PCB FOOTPRINT:




SAW Filter 315.0MHz
Part No: MP07597


Model: TA0657C
Rev No: 2

G. PACKING:

1. Reel Dimension



2. Tape Dimension



SAW Filter 315.0MHz
Part No: MP07597

Model: TA0657C
Rev No: 2

H. RECOMMENDED REFLOW PROFILE:

1. Preheating shall be fixed at 150 ~ 180°C for 60 ~ 90 seconds.
2. Ascending time to preheating temperature 150°C shall be 30 seconds min.
3. Heating shall be fixed at 220°C for 50 ~ 80 seconds and at 260°C +0/-5°C peak (20 ~ 40 sec).
4. Time: 2 times.

