

Product Description

Description:	27.0MHz GXO-3201G/E SM Oscillator
Product family:	GXO-3201
Category:	SM Oscillator
Order code:	MP04453

Features

- ▶ Low current consumption
- ▶ Enable / disable tristate function
- ▶ Miniature ceramic package with metal lid
- ▶ Competitive pricing

Additional Information

For further information regarding packaging, construction, material composition, soldering profile and environment, please refer to **GXO-3201 Product Information sheet**


For dimensions, refer to package drawing: **D0290-A**

Electrical Specifications

Parameter	Value	Notes
Nominal frequency:	27.0MHz	
Frequency stability:	±30ppm max	
Operating temperature range:	-20 to +70°C	
Storage temperature range:	-55 to +100°C	
Supply voltage (V _{DD}):	1.8V ±5%	
Supply current:	2.5mA max	V _{DD} = 1.8V
Driving ability:	15pF CMOS	
Logic levels:	'0' level = 10%V _{DD} max '1' level = 90%V _{DD} min	
Start up time:	10ms max	
Waveform symmetry:	45:55%	@ 50% V _{DD}
Rise / fall time:	7ns max	
Enable / disable times:	10ms / 200ns	
Period jitter RMS:	5ps max	
Phase jitter RMS:	1ps max, 12kHz~20MHz	
Ageing:	±5ppm / year max	

Enable / Disable Function

Input (pad 1)	Output (pad 3)
Open	Enabled
'1' level	Enabled
'0' level	High Impedance



Construction

- ▮ Ceramic body with gold-plated pads
- ▮ Metal lid, seam sealed

Composition



This product is lead-free, and is fully compliant with the RoHS directive 2002/95/EC



Packaging & Handling

Production quantities supplied on T&R, 1k or 3k pcs per reel. Small quantities may be supplied on tape (no reel), or in bulk.



◆ Static sensitive product. Observe proper handling precautions


Marking

FREQUENCY	S	DC
-----------	---	----

Marking type: Laser
DC = Date code in YM, eg "CE" = May 2013


	A	B	C	D	E	F	G	H	J	K	L	M
Y	1	2	3	4	5	6	7	8	9	0		
M	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec

Tape & Reel Specification




Not to scale. Dimensions in mm. Tolerances ±0.1mm unless otherwise stated.

Soldering Profile





Solder resistance: 260°C x 10 secs x 2.






Product Family

GAO-3201, GXO-3201


Construction

-  Ceramic body with gold-plated pads
-  Metal lid, seam sealed

Dimensions (mm)



SOLDER PAD LAYOUT



PAD	CONNECTION
1	Enable/Disable
2	Ground
3	Output
4	Supply