


CC1A-T1A

SM Crystal -55+125°C

- Fundamental mode
- High shock & vibration resistance
- Military temperature range -55+125°C option
- Low power consumption



CONFIGURABLE OPTIONS

Parameter	Option Code
Frequency	
Calibration tolerance	
±50ppm	
Temperature stability / range	
Any	
±50ppm over -40 to +85°C	
±80ppm over -40 to +125°C	
±100ppm over -55 to +125°C	M
Circuit condition	
20pF	

SPECIFICATIONS

Frequency range	8.0 ~ 30.0MHz
Dimensions	8.0 x 3.7 x 1.75mm
Storage temperature range	-55 to +125 °C
Static capacitance (C ₀)	2.0pF typ @ 8.0MHz 2.8pF typ @ 16.384MHz 4.0pF typ @ 24.0MHz
Motional capacitance (C ₁)	4.0fF typ @ 8.0MHz 8.0fF typ @ 16.384MHz 11.0fF typ @ 24.0MHz
Equivalent series resistance	60Ω typ, 100Ω max @ 8.0MHz 35Ω typ, 60Ω max @ 16.384MHz 30Ω typ, 40Ω max @ 24.0MHz
Ageing	±3ppm max first year
Drive level	100μW typ, 500μW max
Shock resistance	±5ppm, 5,000g, 0.3ms, ½ sine
Vibration resistance	±5ppm, 20g, 10.0 ~ 2,000Hz
Soldering condition	Reflow, 260 °C, 20 sec max
Terminations	Gold flashed pads


ORDERING INFORMATION

To request a quotation for the CC1A-T1A please use the configurable options form to choose the options you require and then submit your configured product to our team. Our expert advisers are always happy to help with your requirements and can be contacted on +44 1460 256 100 or at sales@golledge.com.


Following product selection you will be issued with a seven character Golledge part number. Your Golledge part number is the internationally accepted Golledge manufacturing part number (MPN) that should be used for all project documentation, including bills of materials (BoMs) and purchase orders.

If you have any queries regarding any of our documentation our dedicated sales team will be happy to help.

PACKAGE DRAWING



TAPE & REEL SPECIFICATION



A:178* B:16 C:8.5 D:4.4 E:8 F:2 G:80 H:21

*Larger reel size available. Please ask for details

HANDLING & STORAGE



Human Body Model (HBM) 1A (250V to <500V)



Moisture Sensitivity Level (MSL): 1 (or not applicable)

CONSTRUCTION

Ceramic base and lid

COMPLIANCE

Please refer to our **DOCUMENTS** section for more information.



Lead-free (< 0.1% by weight)



RoHS compliant with no exemptions.



REACH compliant.



Free of conflict minerals.



Free from halogens.



Free from ozone-depleting substances.