

# GMCF-45


# 45G30A3

## 45MHz 2 pole crystal filter with

## 30.0kHz 3dB bandwidth

- Custom specifications available
- Fundamental or 3rd overtone modes
- Comprehensive stocks

### **CONFIGURABLE OPTIONS**




Parameter	Option Code
Package	
Any	
UM-1/3L (leaded)	
UM-5/3L (leaded)	
UM-1JN/3L (SMT)	
UM-5JN/3L (SMT)	




Surface mounted

#### SPECIFICATIONS

Centre frequency	45.0MHz	Package
Dimensions	Package options available - see Package Drawing	Thro
Operating temperature range	-20 to +70°C	
Number of poles	2	0.35Ø≯
Pass band	-3dB @ ±15.0kHz min	
Attenuation band	-15dB @ ±50.0kHz max	
In-band ripple	1.0dB max	I
Insertion loss	2.0dB max	
Guaranteed attenuation	-30dB max +500 ~ +1000kHz -30dB max -300 ~ -1000kHz	<ul> <li></li> </ul>
Termination	8000Ω // -1.0pF	
Package style	UM-1/3L, UM-5/3L (through-hole) UM-1JN/3L, UM-5JN/3L (SMT)	Package UM-1/3L UM-5/3L



PACKAGE DRAWING



 Package
 Length L

 UM-1JN/3L
 12.50 max

 UM-5JN/3L
 10.50 max

Dimensions in mm

#### **ORDERING INFORMATION**

To request a quotation for the GMCF-45 45G30A3 please use the configurable options form to choose the options you require and then submit your configured product to our team. Our expert advisers are always happy to help with your requirements and can be contacted on +44 1460 256 100 or at <u>sales@golledge.com</u>.

Following product selection you will be issued with a seven character Golledge part number. Your Golledge part number is the internationally accepted Golledge manufacturing part number (MPN) that should be used for all project documentation, including bills of materials (BoMs) and purchase orders.

If you have any queries regarding any of our documentation our dedicated sales team will be happy to help.

#### **HANDLING & STORAGE**

Height H

8.00 max

6.00 max

7.80



Human Body Model (HBM) 1A (250V to <500V)



Moisture Sensitivity Level (MSL): 1 (or not applicable)



### CONSTRUCTION

Resistance weld

#### COMPLIANCE



Ead-free (< 0.1% by weight )



RoHS compliant with no exemptions. See our

REACH compliant.

See our statement



AulTa Sn W Free of conflict minerals. See our declaration



Free of Halogens. See our declaration

Free of Ozone-depleting substances. <u>See our</u>

declaration