


GSF-74 TY0135A

21.4MHz 3 pole crystal filter with 15.0kHz 3dB bandwidth

- 3-pole filter in one package
- Cost-effective performance
- Frequencies from 21.40 ~ 110MHz available
- Custom specifications available
- Miniature SM package



CONFIGURABLE OPTIONS

Parameter Option Code


The GSF-74 TY0135A has no configurable options.

Please see the specifications table for more details or contact our team today if you have other specification requirements.

SPECIFICATIONS

21.4MHz
7.2 x 5.2 x 1.5mm
-20 to +70°C
3
-3dB @ ±7.5kHz min
-18dB @ ±25.0kHz max
1.0dB max
3.0dB max
-60dB max -910 ±10kHz
1500Ω // 2.5pF
1

PACKAGE DRAWING





ORDERING INFORMATION

To request a quotation for the GSF-74 TY0135A please use the configurable options form to choose the options you require and then submit your configured product to our team. Our expert advisers are always happy to help with your requirements and can be contacted on +44 1460 256 100 or at sales@golledge.com.

Following product selection you will be issued with a seven character Golledge part number. Your Golledge part number is the internationally accepted Golledge manufacturing part number (MPN) that should be used for all project documentation, including bills of materials (BoMs) and purchase orders.

If you have any queries regarding any of our documentation our dedicated sales team will be happy to help.

HANDLING & STORAGE



Human Body Model (HBM) 1A (250V to <500V)



Moisture Sensitivity Level (MSL): 1 (or not applicable)

CONSTRUCTION

Ceramic base with metal lid

COMPLIANCE



Lead-free (< 0.1% by weight)



RoHS compliant with no exemptions.

See our

declaration



REACH compliant. See our statement



Free of conflict minerals. See our declaration



Free of Halogens. See our declaration



Free of Ozone-depleting substances. See our

declaration