
GTXO-76T

Sinewave TCXO High Precision High

Temperature Tristate

- High Precision ±0.05ppm
- High Temperature Operation +105°C
- Tri-state function
- Clipped sine output




CONFIGURABLE OPTIONS	
Parameter	Option Code
Frequency	
Frequency stability	
Any	
±0.05ppm	А
±0.1ppm	В
±0.2ppm	Р
±0.28ppm	D
±0.5ppm	E
±1.0ppm	F
Temperature range	
Any	
-20 to +70°C	N
-40 to +85°C	1
-40 to +95°C	E
-40 to +105°C	D
Supply voltage (V _{DD})	
Any	
+3.3V ±5%	L
+2.5V ±5%	J

^{*}Some combinations of frequency stability and wide temperature ranges may not be available. Our team will advise accordingly if this affects your enquiry.

SPECIFICATIONS

Frequency range	10.0 ~ 52.0MHz
Dimensions	7.0 x 5.0 x 2.1
Storage	-55 to +125°C
temperature	
range	
Supply voltage	±0.1ppm, V _{DD} ±5%
stability	
Load stability	±0.05ppm, Z _L ±10%
Ageing	±1.0ppm max first year
Supply current	5.0mA max
Output waveform	Clipped sine, 0.8V p-p min, +DC offset
Load (Z _L)	10kΩ // 10pF
Start up time	5ms max
Phase noise (typ	-130dBc/Hz @ 100Hz
@ 20.0MHz)	-148dBc/Hz @ 1kHz
	-156dBc/Hz @ 10kHz
Frequency	±1.5ppm max, 60 mins after reflow
Tolerance @25°C	

PACKAGE DRAWING



ORDERING INFORMATION

To request a quotation for the GTXO-76T please use the configurable options form to choose the options you require and then submit your configured product to our team. Our expert advisers are always happy to help with your requirements and can be contacted on +44 1460 256 100 or at sales@golledge.com.

Once we've received your request our expert team will then produce a quotation tailored to meet your needs using the option codes you've selected.

Following product selection you will be issued with a seven character Golledge part number. Your Golledge part number is the internationally accepted Golledge manufacturing part number (MPN) that should be used for all project documentation, including bills of materials (BoMs) and purchase orders.

If you have any queries regarding any of our documentation our dedicated sales team will be happy to help.

MARKING

FREQUENCY
DC


 Pin 1 Marking type: Laser DC = Date code

SOLDERING PROFILE

°C 10s ±5s 260 200 Preheat 150~200°C > 217°C cooldown 60~120s 60~150s Time

Lead free solderability limits: 260°C ±5°C x 10s ±5s x 2.

TAPE & REEL SPECIFICATION



HANDLING & STORAGE



Human Body Model (HBM) 1A (250V to <500V)



Moisture Sensitivity Level (MSL): 1 (or not applicable)

COMPLIANCE



(P6) Lead-free (< 0.1% by weight)



RoHS compliant with no exemptions.

declaration



REACH compliant.



Au Ta Sn W Free of conflict minerals. See our declaration



Free of Halogens. See our declaration



Free of Ozone-depleting substances. See our

declaration