GTXO-C25J

2.5V SM TCXO with CMOS

Output

- 2.5V supply voltage
- Low power consumption
- Enable / disable tristate function
- Low phase noise and jitter
- Excellent frequency stability




CONFIGURABLE OPTIONS	
Parameter	Option Code
Frequency	
Temperature stability	
Any	
±3.0ppm max	К
±2.5ppm max	J
Temperature range	
Any	
0 to +50°C	R
-10 to +60°C	С
-20 to +70°C	N
-30 to +75°C	S
-40 to +85°C	I

SPECIFICATIONS

Frequency range	4.0 ~ 54.0MHz
Dimensions	2.5 x 2.0 x 0.95mm
Calibration tolerance	±2.0ppm @ +25°C ±3°C 60mins after reflow
Storage temperature range	-40 to +125°C
Ageing	±1.0ppm max first year
Supply voltage (V _{DD})	+2.5V (±5%)
Supply	3.1 mA max, 4.0 ~ 10.0MHz
current	3.7mA max, >10.0 ~ 20.0MHz
	4.2mA max, >20.0 ~ 30.0MHz
	4.6mA max, >30.0 ~ 40.0MHz
	5.5mA max, >40.0 ~ 54.0MHz
Frequency vs supply voltage	±0.2ppm, V _{DD} ±5%
Driving ability	15pF CMOS
Logic levels	'0' level = 10%V _{DD} max
	'1' level = 90%V _{DD} min
Waveform symmetry	45:55 @ 50%V _{DD}
Rise / fall time	5ns max
Frequency vs load	±0.2ppm, Z _L ±10%
Enable / disable function	Tristate (control via pad 1)
Standby current	10μA max
Phase noise (typ)	-145dBc/Hz @ 10kHz
Period jitter RMS	3ps typ

PACKAGE DRAWING



PAD	CONNECTION
1	Enable/Disable
2	Ground
3	Output
4	Supply

Dimensions in mm

ORDERING INFORMATION

To request a quotation for the GTXO-C25J please use the configurable options form to choose the options you require and then submit your configured product to our team. Our expert advisers are always happy to help with your requirements and can be contacted on +44 1460 256 100 or at sales@golledge.com.

Following product selection you will be issued with a seven character Golledge part number. Your Golledge part number is the internationally accepted Golledge manufacturing part number (MPN) that should be used for all project documentation, including bills of materials (BoMs) and purchase orders.

If you have any queries regarding any of our documentation our dedicated sales team will be happy to help.

ENABLE / DISABLE FUNCTION

Input (pad 1)	Output (pad 3)				
Open	Enabled				
'1' level	Enabled				
'0' level	High Impedance				


MARKING

S FREQUENCY CTO DC Marking type: Laser

DC = Date Code in YM, eg. "GF" = Jun 2017

	Α	В	С	D	Ε	F	G	Н	J	K	L	М
Υ	1	2	3	4	5	6	7	8	9	0		
M	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec

SOLDERING PROFILE



TAPE & REEL SPECIFICATION

1.1Ø 1.5Ø 8.0 FEED 9.0 ±1.0 ↔ 1.5 ±0.3 120° 21Ø 13Ø 180Ø +0/-3 Dimensions in mm

HANDLING & STORAGE



Human Body Model (HBM) 1A (250V to <500V)



Moisture Sensitivity Level (MSL): 1 (or not applicable)

CONSTRUCTION

Ceramic body with gold-plated pads Metal lid, seam sealed

COMPLIANCE



Lead-free (< 0.1% by weight)



RoHS compliant with no exemptions.

See our

declaration



REACH compliant. See our statement



Free of conflict minerals. See our declaration



Free of Halogens. See our declaration



Free of Ozone-depleting substances. See our

declaration