MCSO2FZ

1.8V Low Jitter Oscillator with -55+125°C Temperature Range

- Low jitter
- Military temperature range -55+125°C option
- Excellent shock & vibration resistance
- Enable / disable tristate option
- Optional tinned pads (Ag/Cu/Zn)




| CONFIGURABLE OPTIONS | |
|------------------------------|-------------|
| Parameter | Option Code |
| Frequency | |
| Frequency stability | |
| * see note below | |
| Any | |
| ±100ppm | |
| ±50ppm | Т |
| Operating temperature range | |
| Any | |
| 0 to +70°C | А |
| -40 to +85°C | В |
| -55 to +125°C | С |
| Enable / disable function | |
| Any | |
| None (pad 1 NC) | |
| Active* (control via pad 1) | E |
| * not available under 500kHz | |
| Terminations | |
| Any | |
| Gold plated pads | |
| Tinned Ag/Cu/Zn | Т |

SPECIFICATIONS

| Frequency range | 10.0kHz ~ 20MHz |
|-----------------------------------|---|
| Dimensions | 5.0 x 3.2 x 1.7mm |
| Supply voltage (V _{DD}) | +1.8V (±5%) |
| Storage temperature range | -65 to +125°C |
| Supply current | 300µA max (@32.768kHz) |
| | 2mA max (≤10MHz) |
| | 3mA max (>10MHz) |
| Driving ability | CMOS |
| Load | 3pF min, 47pF max |
| Logic levels | '0' level = +0.4V max |
| | '1' level = V _{DD} -0.5V min |
| Start up time | 5ms max |
| Waveform symmetry | 40:60 max @ 50%V _{DD} |
| Jitter RMS (1σ) | < 2ps (=20.0MHz) |
| Rise / fall time | 7ns max (15pF, 20~80%V _{P-P}) |
| | 150ns max @ 32.768kHz |
| Shock resistance | 5,000g, 0.3ms ½-sine |
| Vibration resistance | 50g rms 10.0 ~ 2,000Hz |
| Soldering condition | 260°C, 10 sec max |
| | |

PACKAGE DRAWING



A 47nF ceramic capacitor must be connected between GND and VDD

Dimensions in mm

ORDERING INFORMATION

To request a quotation for the MCSO2FZ please use the configurable options form to choose the options you require and then submit your configured product to our team. Our expert advisers are always happy to help with your requirements and can be contacted on +44 1460 256 100 or at sales@golledge.com.

Following product selection you will be issued with a seven character Golledge part number. Your Golledge part number is the internationally accepted Golledge manufacturing part number (MPN) that should be used for all project documentation, including bills of materials (BoMs) and purchase orders.

If you have any queries regarding any of our documentation our dedicated sales team will be happy to help.

ENABLE / DISABLE FUNCTION

| Input (pad 1) | Output (pad 3) |
|---------------|----------------|
| Open | Enabled |
| '1' level | Enabled |
| '0' level | No clock |

Reaction time <1µs

TECHP®INT Golledge

HANDLING & STORAGE

CONSTRUCTION



Human Body Model (HBM) 1A (250V to <500V)

Ceramic base and lid



Moisture Sensitivity Level (MSL): 1 (or not applicable)

COMPLIANCE



Lead-free (< 0.1% by weight)



 $\label{lem:RoHS} \mbox{RoHS compliant with no exemptions.}$

declaration



REACH compliant.



Free of conflict minerals.



Free of Halogens.



Free of Ozone-depleting substances.

declaration